

miniCLOT 4 PLUS

4 CHANNEL COAGULATION ANALYZER

PROTEIN C

AT III

PT

D DIMER

PTT

PROTEIN S FREE

APTT

FIBRINOGEN



SELEO SRL

DIAGNOSTICS FOR HEALTH YOUR PARTNER IN COAGULATION

 **ISO 9001**
LL-C (Certification)



 **ISO 13485**
LL-C (Certification)

Seleo Engineering s.r.l.
1^a traversa bugnano s.c.
81030 Orta di Atella (CE) Italy
TEL +39 (0)81 5022877 FAX +39(0)81 502287702
Homepage www.seleo.it
e-mail info@seleo.it

miniCLOT 4 PLUS

4 CHANNEL COAGULATION ANALYZER

FEATURES

COAGULATION PARAMETERS

- SCREENING TESTS
- CHROMOGENIC TESTS
- TURBIDIMETRIC TESTS
- QUANTITATIVE D DIMER LATEX LIQUID ASSAY
- QUANTITATIVE ATIII CHROMOGENIC LIQUID ASSAY
- FREE PROTEIN S ASSAY
- PROTEIN C ASSAY

LCD COLOR TOUCH SCREEN EASY TO USE WITH AN INNOVATIVE USER FRIENDLY SOFTWARE
 ASSAY SPECIFIC MEMORY CARD PRE-PROGRAMMED WITH CALIBRATION CURVE,
 ASSAY PARAMETERS, PIPETTING VOLUMES AND REAGENTS LOT NUMBERS
 MIXING OF THE PLASMA-REAGENT SOLUTION WITH VIBRATING DEVICE (NO INTERNAL STIRRER)
 QC MENU WITH LEVEY-JENNINGS CHARTS
 ON BOARD PRE-INCUBATION UP TO 20 CUVETTES
 4 THERMOSTATED REAGENT POSITIONS
 2 THERMOSTATED REAGENT POSITIONS WITH MAGNETIC STIRRER



TECHNICAL PARAMETERS

- DIODE LIGHT SOURCES 405 nm
- READING IN ABSORBANCE
- 20 SAMPLES ON BOARD IN PRE-INCUBATION
- REAGENTS ON BOARD THERMOSTATED 4 + 2 WITH AGITATION
- MINIMUM REACTION VOLUME OF 150 μ L
- MEMORY CARD WITH CALIBRATION CURVES
- CALIBRATION CURVE GRAPHICAL REAL-TIME
- AUTO CALIBRATION CURVE AT A POINT
- OPTICAL ZEROING ON PLASMA AND MIX PLASMA-REAGENT
- CURVE REACTION ANALYSIS GRAPHICAL REAL-TIME
- RESULTS in SEC - ACTIVITY% - RATIO - INR - ABSORBANCE

- Q.C. MENU LEVEY JENNINGS CHARTS
- SW REMOTE DIAGNOSTICS YES (OPTIONAL)
- SW MANAGEMENT WITH PATIENTS IN TAO THERAPY YES (OPTIONAL)
- SELF-DIAGNOSTIC SYSTEM
- VIDEO PLOTTING OF CURVES
- VISUAL CONTROL DURING WORK PHASES
- PASSWORD (1,2 OR 3 LEVELS)
- USB PORT FOR DATA TRANSFER OR SOFTWARE UPGRADE
- RJ45 (ETHERNET) PORT FOR LIS INTERFACING
- LANGUAGES : ITALIAN, ENGLISH, FRENCH, SPANISH

DIMENSIONS : 34x22x10 cm
 WEIGHT : 3,0 Kg
 POWER REQUIREMENTS : 90-240V, 50-60 Hz, 80 VA



SELECO SRL

DIAGNOSTICS FOR HEALTH YOUR PARTNER IN COAGULATION



ISO 9001
 LL-C (Certification)



ISO 13485
 LL-C (Certification)

Seleco Engineering s.r.l.
 1^a traversa bugnano s.c.
 81030 Orta di Atella (CE) Italy
 TEL +39 (0)81 5022877 FAX +39(0)81 502287702
 Homepage www.seleco.it
 e-mail info@seleco.it